



DECORATIVE

ENDEAVORS™

STONE, GLASS & METAL MOSAICS

 **daltile**®
IMAGINE WHAT'S POSSIBLE™



Cover photo and above photo feature Endeavors™ Neo Classic 5/8 x random mosaic on the wall.

On-Trend Confidence

Perfect for a transitional design, this linear mosaic features metal, glass, and stone that adds unassuming confidence to your space. Create an accent wall or limit it to the backsplash to add a hint of color and metallic luster to the kitchen, bathroom, or even outside.

- MIXED MEDIA
 - Stone, glass, and metal blend into a mosaic that stands out without being overbearing
 - Mixed materials add interest to transitional and contemporary designs
- VERSATILE APPLICATION
 - Suitable for walls in all spaces including outdoor applications
 - 13 x 12 mesh-mounted sheets with interlocking edges for a seamless look

Professional
TILE SOLUTIONS

USAGE

Floors

Walls

Countertops



W



5/8 X RANDOM MOSAIC



AVANT GARDE F163



NEO CLASSIC F164



MYSTIC F161



ZEN F162



SPIRIT F159



MEDITATION F158



SITAR F160



TAMBURA F157

DECORATIVE

ENDEAVORS™

STONE, GLASS & METAL MOSAICS

SIZES

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	5/8 x Random Mosaic (Mesh-mounted)	(13" x 11-7/8" Sheet) (33.00 cm x 30.00 cm Sheet)	5/16"	9.60	10

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	


A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

Suitable for use in wet areas such as shower walls.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" Approximately	 Random (V4)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: daltille.com/information/TestResults.

NOTES

Since there are variations in all glass products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.2 standards.

For additional information refer to "Factors to Consider" at: daltille.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.



DESIGNED TO HELP EARN LEED™ CREDITS. For more detailed information, visit daltillegreenworks.com.

7834 C. F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltille® products and information, visit our website at daltille.com.



IMAGINE WHAT'S POSSIBLE™

©2017 Daltille (9/17)