



FLOOR

**EXHIBITION™**  
COLORBODY™ PORCELAIN

 **daltile®**  
IMAGINE WHAT'S POSSIBLE™



Cover photo features Trend Grey and Fray 12 x 24 field tile in a grid pattern on the floor. Above photo features Trend Grey and Fray 12 x 24 in a staggered brick-joint pattern.

## Make Your Space a Work of Art

Exhibition™ from Daltile takes its inspiration from trendy art galleries and stylish exposés. It takes on two looks, intricate linen fabric and cement, for a distinct and expressive appearance. When combined, these two visuals coordinate and complement each other perfectly. Exhibition's artistic personality pairs especially well with large and contemporary spaces. And its warm and cool color tones complement the most diverse palettes.

- ARTISTIC ELEMENTS
  - Give your space a unique and modern look inspired by textiles and concrete
- TRENDY SIZES
  - Ideal for large projects and open spaces
- COLORS THAT COMPLEMENT
  - Select from an array of cool and warm tones that pair perfectly
- HIGH-END & HARD WEARING
  - Rich aesthetic with unparalleled durability

 PRE-CONSUMER  
RECYCLED MATERIALS

 TRU-EDGE

 CERTIFIED  
PORCELAIN  
TILE  
0.9% or less water absorption



FIELD TILE



BORREL EX11



STARK WHITE EX01



MODE BEIGE EX06



GREY EX02



TREND GREY EX03



TAILOR BEIGE EX07



MODERN TAN EX08




ECRU EX12



FRAY EX10



DARK GREY EX04



BLACK EX05






TWILL EX09

# EXHIBITION™



COLORBODY™ PORCELAIN

## SIZES - CEMENT VISUAL

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	24 x 48 Field Tile (Unpolished)	(23-3/8" x 46-7/8") (59.50 cm x 119.20 cm)	3/8"	15.50	2
	24 x 24 Field Tile (Unpolished & Textured*)	(23-3/8" x 23-3/8") (59.50 cm x 59.50 cm)	3/8"	11.64	3
	12 x 24 Field Tile (Unpolished & Textured)	(11-5/8" x 23-3/8") (29.65 cm x 59.50 cm)	3/8"	9.70	5

\* 24 x 24 textured field tile is available via special order. Contact your local sales representative for more information.

## SIZES - FABRIC VISUAL

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	24 x 24 Field Tile (Unpolished)	(23-3/8" x 23-3/8") (59.50 cm x 59.50 cm)	3/8"	11.64	3
	12 x 24 Field Tile (Unpolished)	(11-5/8" x 23-3/8") (29.65 cm x 59.50 cm)	3/8"	9.70	5

## FLOOR APPLICATIONS - CEMENT VISUAL

	Target DCOF wet	Suitable
Dry & Level – Interior	N/A	✓
Wet & Level – Interior	≥ 0.42	✓
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	✓*
Ramps & Inclines	≥ 0.65	✓*

\* Textured surface only

## FLOOR APPLICATIONS - FABRIC VISUAL

	Target DCOF wet	Suitable
Dry & Level – Interior	N/A	✓
Wet & Level – Interior	≥ 0.42	✓
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	
Ramps & Inclines	≥ 0.65	


A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit [daltile.com/DCOF](http://daltile.com/DCOF).

## TRIM

	Type	Number	Size	Pieces per Carton
	Bullnose	S-43C9	3 x 12	30
	Cove Base	S-36C9T	6 x 12	20
	Cove Base Outcorner	SC-36C9T	1 x 6	10

Floor bullnose, cove base, and cove base corner trim are intended to coordinate with floor field tile in the standard 90-degree installation position.

## INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when multiple sizes are installed in a modular pattern, and when installed in a staggered brick-joint pattern; overlap should not exceed 33%)	 High (V3)

## TEST RESULTS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 450 lbs.
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

## NOTES

Special consideration needs to be given when installing tiles greater than 15". Please refer to [daltile.com/LargeTiles](http://daltile.com/LargeTiles) for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at [daltile.com/Factors](http://daltile.com/Factors).



DESIGNED TO HELP EARN LEED™ CREDITS. For more detailed information, visit [daltilegreenworks.com](http://daltilegreenworks.com).



SCAN QR CODE FOR PRODUCT INFORMATION

Get a QR Code reader at: [GET.DALTILE.COM](http://GET.DALTILE.COM)



7834 C. F. Hawn Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at [daltile.com](http://daltile.com).



IMAGINE WHAT'S POSSIBLE™

©2016 Dal-Tile Corporation (6/16)