



FLOOR | WALL

SEVERINO™

GLAZED CERAMIC with REVEAL IMAGING®

 **daltile®**
IMAGINE WHAT'S POSSIBLE™



Cover photo features Severino™ Cenere Fog 18 x 18 floor tile on the floor, Cenere Fog 10 x 14 wall tile and 2 x 2 mosaic on the wall. Above photo features Severino™ Cenere Fog 18 x 18 floor tile on the floor and Cenere Fog 2 x 2 mosaic on the wall.

Contemporary Interpretation of Established Stone Looks

Taking its cue from the tumbling cliffs of the Amalfi Coast, Severino is a beautiful mix of travertine and marble looks designed to add visual warmth with its natural beauty. Severino differentiates itself with a rich, stone graphic and an organic color palette. Offered in four colors and seven versatile sizes, including a 2 x 2 pressed mosaic and 2-inch octagonal mosaic, Severino exhibits relaxed sophistication.

- **IMAGINATIVE DESIGN**
 - Contemporary take on a classic stone look in four natural colors
 - Smooth travertine and marble graphics achieved through Reveal Imaging® technology
- **UNIFYING COMBINATIONS**
 - Decorative wall accent, mosaics and trim coordinate with floor and wall tile
 - Organic color palette that harmonizes any space



POST-CONSUMER RECYCLED MATERIALS



PRE-CONSUMER RECYCLED MATERIALS



MADE IN THE U.S.A.



REVEAL IMAGING®

All or select items within this series meet the requirements for these qualifications. For more product information, visit daltile.com.

FLOOR & WALL TILE




VENTO BREEZE SV96



ARIA SAND SV97



CENERE FOG SV98



TERRA BRUNO SV99



2" OCTAGON & 1" DOT MOSAIC



VENTO BREEZE SV96



ARIA SAND SV97



CENERE FOG SV98



TERRA BRUNO SV99

2 x 2 MOSAIC



VENTO BREEZE SV96



ARIA SAND SV97



CENERE FOG SV98



TERRA BRUNO SV99

DECORATIVE WALL ACCENTS



CESTINO FRESCO SV94
(COORDINATES WITH SV96 & SV98)











CESTINO CALDO SV95
(COORDINATES WITH SV97 & SV99)

SEVERINO™

GLAZED CERAMIC with REVEAL IMAGING®

SIZES

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	18 x 18 Floor Tile	(17-1/2" x 17-1/2") (44.45 cm x 44.45 cm)	5/16"	17.04	8
	12 x 24 Floor Tile	(11-9/16" x 23-3/8") (29.40 cm x 59.30 cm)	3/8"	15.04	8
	12 x 12 Floor Tile	(11-13/16" x 11-13/16") (30.00 cm x 30.00 cm)	5/16"	14.55	15
	10 x 14 Wall Tile	(9-13/16" x 13-15/16") (24.99 cm x 35.40 cm)	5/16"	14.25	15
	6 x 6 Wall Tile	(6" x 6") (15.31 cm x 15.31 cm)	5/16"	12.50	50
	2 x 10 Decorative Wall Accent	(1-3/4" x 9-7/8") (4.50 cm x 24.90 cm)	1/4"	N/A	6
	2 x 2 Mosaic (Dot-mounted on 12" x 24" Sheet)	(12" x 24" Sheet) (30.48 cm x 60.96 cm Sheet)	1/4"	24.00	12
	2" Octagon with 1" Dot Mosaic (Dot-mounted on 12" x 12" Sheet)	(12" x 12" Sheet) (30.48 cm x 30.48 cm Sheet)	1/4"	10.00	10

FLOOR APPLICATIONS

(Excludes Wall Tile)	Target DCOF wet	Suitable
Dry & Level – Interior	N/A	✓
Wet & Level – Interior	≥ 0.42	✓*
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	
Ramps & Inclines	≥ 0.65	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

OTHER APPLICATIONS

	Suitable
Walls/Backsplashes	✓
Countertops	✓**
Pool Linings	✓***

APPLICATION NOTES:

- * Mosaics only. Mosaics also suitable for residential and light commercial shower floors.
 - ** Floor tile, 6 x 6 wall tile and mosaics only
 - *** 6 x 6 wall tile and mosaics only
- Suitable for exterior applications in non-freezing climates only when proper installation methods are followed.










DESIGNED TO HELP EARN LEED™ CREDITS. For more detailed information, visit daltillegreenworks.com.

SCAN QR CODE FOR PRODUCT INFORMATION

Get a QR Code reader at: GET.DALTILE.COM




TRIM

	Type	Number	Size	Pieces per Carton
	Floor Bullnose ■	P-43C9	3 x 12	22
	Wall Bullnose	S-4269 (6" side)	2 x 6	100
	Wall Bullnose Corner	SN-4269	2 x 2	25
	Wall Bullnose	S-4310 (10" side)	3 x 10	54
	Wall Bullnose Corner	SN-4310	3 x 3	32
	Quarter Round	A-106	1 x 6	152
	Quarter Round Corner	UC-106	1 x 1	40

■ Floor bullnose is intended to coordinate with floor tile in the standard 90-degree installation position.

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (overlap should not exceed 33% when installing tile with a length of 15" or greater in a staggered brick-joint pattern) Wall: 1/16"; Mosaics: 1/8"	 High (V3)

TEST RESULTS

	ASTM#	Floor Result	Wall Result	Mosaic Result
Water Absorption	C373	< 7.0%	< 20.0%	< 3.0%
Breaking Strength	C648	> 250 lbs	120-230 lbs	> 250 lbs
Scratch Hardness	MOHS	8.0	4.0-6.0	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant
Abrasion Resistance	C1027	3	N/A	3

For additional information, visit daltille.com/information/TestResults.

NOTES

Manufacturer Advisory: These tiles have a dynamic coefficient of friction < 0.42 as measured by the DCOF Acutest method. Tiles with DCOF values < 0.42 are not recommended for use in areas with wet or slippery conditions. For more information, see ANSI standard A137.1 section 6.2.2.1.10, available at www.tileusa.com.

Special consideration must be given when installing tiles greater than 15 inches. Please refer to daltille.com/LargeTiles for more information.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at daltille.com/Factors.

7834 C. F. Hawn Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltille® products and information, visit our website at daltille.com.



IMAGINE WHAT'S POSSIBLE™

©2017 Daltille (1/17)